



1998NA

AUDIO PORTER SWITCHBOARD. S1



Audio porter switchboard in desk version for Simplebus 1 system with microswitch keypad and 32-character alphanumeric display. Ergonomic handset with easier hangup, thanks to concealed magnetic panels. Allows the code and name of the called and calling users to be displayed, keeping unanswered calls stored in the memory. Manages Day/Night mode and user/user intercom service. Allows management of alarm indications originating from users. Up to 1000 users can be saved. Supplied with a removable cable with connection hub. 24 VAC power supply with art. 1195. Dimensions (L x H x D): 225x100x225 mm.



1998NA

AUDIO PORTER SWITCHBOARD. S1

COMPATIBLE SYSTEMS

Audio/video Simplebus 1	Yes
Audio Simplebus 1	Yes

DISPLAY

Display type	32-character alphanumerical display
--------------	-------------------------------------

AUDIO FEATURES

Technologies implemented	Full-Duplex
--------------------------	-------------

ELECTRICAL CHARACTERISTICS

Max/min absorption (mA)	20 ÷ 200
Type of power supply	External power supply

HARDWARE FEATURES

Visual signalling	Yes
Number of push-buttons (n°)	36
Acoustic signalling	Yes
Number of outputs (n°)	2

ENVIRONMENTAL AND COMPLIANCE FEATURES

Environmental class	I
---------------------	---

MAIN FUNCTIONS

Door opener	Yes
-------------	-----

GENERAL FEATURES

Call type	Digital
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
Type of buttons	Mechanical



1998NA

AUDIO PORTER SWITCHBOARD. S1

MAIN FEATURES

Height (mm)	90
Depth (mm)	230
Product weight (g)	1500
Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 90
Supply voltage	24
Maximum current absorption (mA)	200

SOFTWARE/FIRMWARE SPECIFICATIONS

No. of storable users (n°)	1000
----------------------------	------

GENERAL DATA

Type of finishing materials	ABS
-----------------------------	-----

FUNCTIONS

Alarm function	Yes
Actuator control function	Yes
Intercom function	Yes
Key button function	Yes

CONNECTIVITY

RS232 ports (n°)	1
------------------	---