

DATA SHEET

COD. **2603U**

STYLE SERIES UNIVERSAL SYSTEM BASIC INTERCOM

Universal door-entry phone, compatible with most of the door-entry phones produced by leading international manufacturers. Ideal in door-entry phone system replacements and repairs. Speech button on base unit, call volume adjustment and privacy function. Features a lock-release button and an extra button for additional services with independent common. Features loudspeaker volume control and microphone volume control to meet all possible requirements, can be used for systems with positive common or systems with negative common, can replace door-entry phones with condenser microphone and carbon capsule, features electronic calling or mechanical calling by means of a buzzer. Supplementary buttons or LEDs cannot be added for this model. Dimensions: 95x215x58 mm.



Main specifications

Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	No
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	No
Induction loop function:	No
B/W or colour display:	-
Product colour:	White RAL9003
Interchangeable cover:	No
Sensitive Touch technology:	No
Total buttons:	2
Backlighting color:	-

Functions

Actuator control function:	No
Switchboard call function:	No
Intercom function:	No
Privacy function:	Yes
Redial:	No
Floor door call function:	No
Electronic bell:	Yes
Mechanical ringtone:	Yes
Customisable ringtone:	No
Alarm function:	No
Privacy conversation function:	Yes

DATA SHEET

Key button function:	Yes
----------------------	-----

Hardware specifications

Customisable housing:	No
-----------------------	----

Settings

Loudspeaker volume control:	Yes
-----------------------------	-----

Microphone volume control:	Yes
----------------------------	-----

Ringtone volume control:	Yes
--------------------------	-----

General data

Product height (mm):	215
----------------------	-----

Product width (mm):	95
---------------------	----

Product depth (mm):	58
---------------------	----

Compatibility

Traditional system:	Yes
---------------------	-----

Technical specifications

IP Rating:	IP30
------------	------

Operating temperature (°C):	-5 ÷ 40
-----------------------------	---------

Product weight (g):	0,429
---------------------	-------

Clamps:	A B C D E C2 P2
---------	-----------------