

深圳市华特威科技有限公司

HONGKONG FIRSTWELL TECH CO.,LIMITED

PADRYn2



Time Management Solution with Android or Linux OS





Key Features

- 7" Multi-Touch LCD Screen
- Multiple Events Management
- Standalone Employee's Shift & Schedule Management Function
- Self-Service Report and Data Management
- Multi verification (Fingerprint, RFID, password)
- Web Browser Management
- Equipped With Backup Battery Responsive interface
- Time Attendance Management Apps
- ID Camera up to 5MP
- HDMI out for external screen
- 4xUSB port
- Bluetooth 4.2
- Anti-vandal metal case

PADRYn2 is Firstwell newest multi-functional data collection terminal, with Android 6.0.1or Linux platform, with newly integrated SILK ID fingerprint sensor and/or RFID module.

Equipped with and internal battery and 7" touch screen display, PADRYn2 has added features as its wireless communications via Wi-Fi, Bluetooth it offers a variety of identification and information management solutions.

PADRYn2 comes in two different versions: PADRYn2 RFID and PADRYn2F with Finger print sensors

In combination with Cloud solution, your attendance and employee data will be always available in secure cloud servers. Users will have access to attendance events and management, being able to set different user privileges.





深圳市华特威科技有限公司

HONGKONG FIRSTWELL TECH CO.,LIMITED











PADRYn2 Time Management Solution with Android or Linux OS

Specifications

Model		PADRYn2	PA	DRYn2F	
Hardware	OS	Android 6.0.1 or Linux depend of order			
	CPU	Broadcom BCM2837B0, quad-core Cortex-A53 (ARMv8) 64-bit SoC @ 1.4GHz			
	Memory RAM	1GB LPDDR2 SDRAM			
	Storage	Include 16GB			
	Communication	2.4GHz and 5GHz IEEE 802.11.b/g/n/ac wireless LAN, RJ45 LAN 10/100Mbps, Bluetooth 4.2, BLE, RJ45			
		Gigabit Ethernet over USB 2.0 (maximum throughput 300 Mbps)			
	USB	4 USB 2.0 ports			
	HDMI	Full-size HDMI Graphic card integrated			
	Storage	Micro SD port			
	Fingerprint Sensor	No	Silk	kID fingerprint sensor	
	LCD screen	7-inch 1024x600			
	Touch panel	Capacitive Touch			
	Gravity sensor	Yes (+2g)			
	Alarm Trigger	conflict			
	Battery	Yes (4 hours)			
Interface	Camera	5Mpx front camera, automatic photo applying			
	Speaker audio	Integrated, Power 0.8W + Aud	Integrated, Power 0.8W + Audio out		
	Microphone	Single-end			
	RFID module	Integrated: 125Khz/EM / 13.56Mhz MF / S127(optional) / NFC			
General	Operating Conditions	Temperature: -0°C – 55°C Humidity: 95% or less (non-condensing)			
	Power Supply	160~240 VAC / DC12V / Power-over-Ethernet (PoE) support			
	Power Consumption	Max. 12W			
	Dimension	240x130x45mm			
	Ingress Protection	IP54, metal or ABS case, depend on the order, wall or table mounting			
	Warranty	36 month factory warranty			
	Version	RFID	RF	ID + Finger Print	

