



Test Report: GS120A20

120W AC-DC Single Output Desktop

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST*-

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 150 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 50.4 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1 : 5%~ -5% (Max)	I/P : 100 VAC / 264 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 1.8%~ -1.8%	P
3	LINE REGULATION	V1 : 1%~ -1% (Max)	I/P : 100VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0.63%~ -0.63%	P
4	LOAD REGULATION	V1 : 5%~ -5% (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 1%~ -1%	P
5	SET UP TIME	230VAC : 2000 ms (Max) 115VAC : 2500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 297 ms 115VAC/ 594 ms	P
6	RISE TIME	230VAC : 25 ms (Max) 115VAC : 25 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 14 ms 115VAC/ 12 ms	P
7	HOLD UP TIME	230VAC : 20 ms (TYP) 115VAC : 20 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 70 ms 115VAC/ 29 ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : < 5%	P
9	DYNAMIC LOAD	V1 : 2000 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1). 440 mVp-p (2). 607 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	100VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE-3V= 97 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	70 V~264V TEST : OK	P
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 264 VAC O/P : FULL -MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.97 / 230 VAC(TYP) 0.99 / 115 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.981 / 230 VAC PF= 0.99 / 115 VAC	P
4	EFFICIENCY	90 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	90.24 %	P
5	INPUT CURRENT	230V/ 0.7 A (TYP) 115V/ 1.4 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I= 0.57 A/ 230 VAC I= 1.15 A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 70 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I= 58 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 0.75 mA / 240 VAC	I/P : 240 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.22 mA N-FG : 0.22 mA	P
8	NO LOAD CONSUMPTION	< 0.5 W	I/P : 230VAC O/P : NO LOAD Ta : 25°C	< 0.38 W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 % ~ 135 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	115 %/ 230 VAC 138 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1 : 21V ~27 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	23.54 V/ 230 VAC 23.54 V/ 115 VAC Shut down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	SPEC : RTH2>100 °C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down Re-power ON	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q3 Rated : SPA11N65C3 11A/650V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 604 V (2) 488 V (3) 600 V	P
2	Diode Peak Voltage	Q101 Rated : IRF3415 43A/150V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 150 V (2) 143 V (3) 139 V	P
3	Input Capacitor Voltage	C5 Rated : 120u/400V 105°C 18*31.5 VZ	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 384.1 V (2) 370.5 V (3) 370.7 V	P
4	Control IC Voltage Test	U1 Rated : TEA1791T 8.85V~38V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 17.655 V (2) 17.596 V (3) 17.595 V	P
5	Power Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated : IRFB20N50K 20A/500V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 462 V (2) 394 V (3) 436 V	P

■ SAFETY & E.M.C. TEST
SAFETY TEST


NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min	I/P-O/P : 3.6 KVAC/min Ta : 25°C	I/P-O/P : 4.59 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ	I/P-O/P : 500 VDC Ta : 25°C / 70%RH	I/P-O/P : 22.2 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	9mΩ	P
4	APPROVAL	TUV : Certificate NO : S50185150 UL : File NO :			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS D	I/P : 230 / 220/240VAC/50HZ O/P : 100/75/50/25% LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 EN61204-3 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT		VERDICT																																																																																															
				Position	Temp																																																																																																
1.	THERMO TRACER TEST (ROOM AMBIENT)	MODEL:GS120A24 TEST CONDITION: 90V FULL LOAD TA=23°C  <p>98210004. IRI (定點測溫)</p> <p>熱顯像調整 自動調整</p> <p>座標: 22, 14 原資料溫度: 23.4°C (EO.94) 放射率: 0.94 補正後溫度: 23.4°C (EO.94) 環境溫度: 21.6°C</p> <p>高溫 113.7°C 低溫 2.6°C</p> <p>最高溫(H): 104.1°C 座標: 291, 73 最低溫(L): 21.6°C 座標: 224, 65 全域放射率: 0.94</p> <p>日期: 2009/ 8/21 時間: 14: 2:26</p>	p 1: 104.1°C 291x, 73y p 2: 77.0°C 246x, 164y p 3: 75.3°C 191x, 164y p 4: 23.3°C 169x, 163y p 5: 73.4°C 135x, 163y p 6: 67.3°C 54x, 165y p 7: 22.3°C 233x, 98y p 8: 85.4°C 136x, 142y p 9: 68.4°C 144x, 90y p10: 64.6°C 79x, 109y p11: 57.0°C 15x, 107y p12: 63.7°C 132x, 76y p13: p14: p15:	1	RTH1	104.5	P																																																																																														
				2	BD1	77																																																																																															
				3	Q1	75.3																																																																																															
				4	D1	23.3																																																																																															
				5	Q3	73.4																																																																																															
				6	Q101	67.3																																																																																															
				7	L3	22.3																																																																																															
				8	D2	85.4																																																																																															
				9	C5	85.4																																																																																															
				10	T1	64.6																																																																																															
				11	LF-100	57																																																																																															
				12																																																																																																	
				13																																																																																																	
				14																																																																																																	
				15																																																																																																	
				2	TEMPERATURE RISE TEST	MODEL : GS120A12 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P : 230VAC O/P : FULL LOAD Ta= 31.1 °C 2. HIGH AMBIENT BURN-IN : 21 HRS I/P : 230VAC O/P : FULL LOAD Ta= 50.9 °C		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 31.1 °C</th> <th>HIGH AMBIENT Ta= 50.9 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>TR962</td><td>65.5°C</td><td>81.5°C</td></tr> <tr><td>2</td><td>LF2</td><td>TR781-R2</td><td>66.5°C</td><td>83.0°C</td></tr> <tr><td>3</td><td>C11</td><td>474/450V 10% P=10 MMX</td><td>71.6°C</td><td>88.6°C</td></tr> <tr><td>4</td><td>BD1</td><td>4A/800V GBU408</td><td>70.4°C</td><td>86.7°C</td></tr> <tr><td>5</td><td>D5</td><td>3A/600V 1N5406</td><td>75.9°C</td><td>92.4°C</td></tr> <tr><td>6</td><td>C5</td><td>120u/420V 105°C PT</td><td>77.4°C</td><td>93.5°C</td></tr> <tr><td>7</td><td>Q1</td><td>IRFB20N50K 20A/500V TO220</td><td>76.8°C</td><td>92.7°C</td></tr> <tr><td>8</td><td>D2</td><td>2A/800V GP20K</td><td>98.2°C</td><td>118.0°C</td></tr> <tr><td>9</td><td>Q3</td><td>SPA11N65C3 11A/650V</td><td>83.6°C</td><td>100.5°C</td></tr> <tr><td>10</td><td>C41</td><td>82u/35V L5kh KY</td><td>83.1°C</td><td>99.1°C</td></tr> <tr><td>11</td><td>C42</td><td>22u/50V UL10Kh YXM</td><td>86.1°C</td><td>102.3°C</td></tr> <tr><td>12</td><td>U1</td><td>PFC FAN6921MR</td><td>77.4°C</td><td>91.8°C</td></tr> <tr><td>13</td><td>RTH2</td><td>NTC 100KΩ 3Φ TTC3A104F4193EY 1%</td><td>81.1°C</td><td>97.2°C</td></tr> <tr><td>14</td><td>L1</td><td>TR623-R3</td><td>73.4°C</td><td>89.9°C</td></tr> <tr><td>15</td><td>L3</td><td>TF2125</td><td>74.0°C</td><td>90.3°C</td></tr> <tr><td>16</td><td>T1</td><td>TF2128</td><td>95.3°C</td><td>111.0°C</td></tr> <tr><td>17</td><td>Q101</td><td>IRFB3607PBF 80A/75V</td><td>82.9°C</td><td>99.3°C</td></tr> <tr><td>18</td><td>CASE</td><td>UP CASE</td><td>89.4°C</td><td>75.9°C</td></tr> </tbody> </table>	NO	Position	P/N	ROOM AMBIENT Ta= 31.1 °C	HIGH AMBIENT Ta= 50.9 °C	1	LF1	TR962	65.5°C	81.5°C	2	LF2	TR781-R2	66.5°C	83.0°C	3	C11	474/450V 10% P=10 MMX	71.6°C	88.6°C	4	BD1	4A/800V GBU408	70.4°C	86.7°C	5	D5	3A/600V 1N5406	75.9°C	92.4°C	6	C5	120u/420V 105°C PT	77.4°C	93.5°C	7	Q1	IRFB20N50K 20A/500V TO220	76.8°C	92.7°C	8	D2	2A/800V GP20K	98.2°C	118.0°C	9	Q3	SPA11N65C3 11A/650V	83.6°C	100.5°C	10	C41	82u/35V L5kh KY	83.1°C	99.1°C	11	C42	22u/50V UL10Kh YXM	86.1°C	102.3°C	12	U1	PFC FAN6921MR	77.4°C	91.8°C	13	RTH2	NTC 100KΩ 3Φ TTC3A104F4193EY 1%	81.1°C	97.2°C	14	L1	TR623-R3	73.4°C	89.9°C	15	L3	TF2125	74.0°C	90.3°C	16	T1	TF2128	95.3°C	111.0°C	17	Q101	IRFB3607PBF 80A/75V	82.9°C	99.3°C	18	CASE	UP CASE
NO	Position	P/N	ROOM AMBIENT Ta= 31.1 °C				HIGH AMBIENT Ta= 50.9 °C																																																																																														
1	LF1	TR962	65.5°C				81.5°C																																																																																														
2	LF2	TR781-R2	66.5°C				83.0°C																																																																																														
3	C11	474/450V 10% P=10 MMX	71.6°C				88.6°C																																																																																														
4	BD1	4A/800V GBU408	70.4°C				86.7°C																																																																																														
5	D5	3A/600V 1N5406	75.9°C				92.4°C																																																																																														
6	C5	120u/420V 105°C PT	77.4°C				93.5°C																																																																																														
7	Q1	IRFB20N50K 20A/500V TO220	76.8°C				92.7°C																																																																																														
8	D2	2A/800V GP20K	98.2°C				118.0°C																																																																																														
9	Q3	SPA11N65C3 11A/650V	83.6°C				100.5°C																																																																																														
10	C41	82u/35V L5kh KY	83.1°C				99.1°C																																																																																														
11	C42	22u/50V UL10Kh YXM	86.1°C				102.3°C																																																																																														
12	U1	PFC FAN6921MR	77.4°C				91.8°C																																																																																														
13	RTH2	NTC 100KΩ 3Φ TTC3A104F4193EY 1%	81.1°C				97.2°C																																																																																														
14	L1	TR623-R3	73.4°C				89.9°C																																																																																														
15	L3	TF2125	74.0°C				90.3°C																																																																																														
16	T1	TF2128	95.3°C				111.0°C																																																																																														
17	Q101	IRFB3607PBF 80A/75V	82.9°C	99.3°C																																																																																																	
18	CASE	UP CASE	89.4°C	75.9°C																																																																																																	
3	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 108 % LOAD Ta : 25°C	TEST : OK		P																																																																																															

4	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -30 °C	TEST : OK	P
5	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 45 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 45 °C HUMIDITY= 95 %R.H	TEST : OK	P
6	TEMPERATURE COEFFICIENT	± 0.03 %(0-50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.015 %(0-50°C)	P
7	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P
8.	THERMAL SHOCK TEST	1. Thermal shock Temperature : -35 °C~ +50°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK	P
9	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10-500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C		TEST : OK	P
10	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 50 °C LIFE TIME		(1) 41493.6 HRS (2) 10281.6 HRS (3) 26560.8 HRS	P
11	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 400.7K HRS			P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2010/4/18	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2010/6/5	PRODUCT SAMPLE	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023