3453S

STAINLESS STEEL SBC 316 TOUCH A/V ENTRANCE PANEL

SB TOP

Stainless steel flush-mounted entrance panel (fitted level with the wall) with 8" capacitive touch screen featuring high visibility and impact-proof glass. Certified as IK08. Operation with configurable graphics (list of names with search, virtual static buttons up to 10 users, alphabetised directory, number code up to 8 digits). Allows customisation of the virtual buttons. It can be used in conjunction with Simplekey electronic keys for automatic updating of names in the directory. Users and settings are simple to program using VIP Manager software. It is compatible with all SBTOP products and functions. Complete with a/v unit Art. 4680C for audio/video/door lock management, and flush-mounted box with concealed fixing screws. Dimensions 342x182x3 mm

AWARDS

DESIGN MILANO

reddot design award

GOOD DESIGN

Merlion Awards

The technical specifications are subject to variations without warning.

3453S

STAINLESS STEEL SBC 316 TOUCH A/V ENTRANCE PANEL

MAIN FEATURES

Type of display:	Touch 8"
Audio/video system:	Yes
Flush-mounted:	Yes
Lens size (mm):	3,6
Signal/noise ratio (dB):	48
Camera orientation:	Yes
Clamps:	L L V+V- RTE DO PR GND SE COM NC NO
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55
Vandal Resistant rating (IK code):	IK08

FUNCTIONS

Key button function:	Yes

HARDWARE SPECIFICATIONS

Visual signalling:	Yes
Acoustic signalling:	Yes

GENERAL DATA

Product height (mm):	342
Product width (mm):	182
Product depth (mm):	3

COMPATIBILITY

Simplebus Top audio/video system:	Yes

The technical specifications are subject to variations without warning.

3453S

STAINLESS STEEL SBC 316 TOUCH A/V ENTRANCE PANEL

ACCESSORIES

3458
ACCESS CONTROL ACCESSORY MODULE FOR EXTERNAL UNITS, 316
Flush-mounted 3 mm thick stainless steel plate for housing the access control module. Can be used in conjunction with all entrance panels in the 316 range. Dimensions 88x182x3 mm

3460/2
FLUSH-MOUNTED BOX FOR 1- AND 2-BUTTON ENT.PANELS. 316 SERIES
Flush-mounted box for 1- and 2-button ent. panels from 316 Analog series. Dimensions: 164x227.5x56 mm

3460/4
FLUSH-MOUNTED BOX FOR 3- AND 4-BUTTON ENT.PANELS. 316 SERIES
Flush-mounted box for 3- and 4-button ent. panels from 316 Analog series. Dimensions: 164x273.5x56 mm

3460/6
FLUSH-MT.BOX FOR TOUCH-SENSE & 5-6 BUTT.ENT.PAN. 316 SERIES
Flush-mounted box for 5- and 6-button ent. panels from 316 Analog series and for 316 Touch and 316 Sense series ent. panels. Dimensions: 164x323x56 mm

3460/9
FLUSH-MOUNTED BOX FOR 7-8-9-BUTTON ENT. PANELS. 316 SERIES
Flush-mounted box for 7-, 8- and 9-button ent. panels from 316 Analog series. Dimensions: 164x388.5x56 mm

3460/12
FLUSH-MOUNTED BOX FOR 10-11-12-BUTTON ENT.PANELS. 316 SERIES
Flush-mounted box for 10-, 11- and 12-button ent. panels from 316 Analog series. Dimensions: 164x457.5x56 mm

The technical specifications are subject to variations without warning.

3453S

STAINLESS STEEL SBC 316 TOUCH A/V ENTRANCE PANEL

ACCESSORIES

|		
	3462/2	**WALL-MOUNTED HOUSING SERIES 316 1 & 2 BUT. PANEL** Stainless steel accessory for wall-mounted 316 series entrance panels with 1 or 2 buttons. Dimensions 180x245x57 mm
	3462/4	**WALL-MOUNTED HOUSING SERIES 316 3 & 4 BUT. PANEL** Stainless steel accessory for wall-mounted 316 series entrance panels with 3 or 4 buttons. Dimensions 180x290x57 mm
	3462/6	**WALL HOUSING FOR TOUCH-SENSE & 5-6 BUTT.ENT.PAN. 316 SERIES** Stainless steel accessory for wall-mounted entrance panels Art. 3451, 3451/A, 3452, 3453, 3454. Dimensions 180x340x57 mm
	1220	**NAME TAG SHEETS FOR 316 ANALOG ENTRANCE PANEL** The kit contains 10 sheets of adhesive labels for nameplates and 7 sheets for information modules.
	1235A	**NAMEPLATE LABEL PRINTING SOFTWARE** Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website
	1596B	**POWER SUPPLY 33VDC 60W 100-240VAC, PSE CERTIFIED** Power supply unit with 110-230 VAC primary and 33 VDC / 1.8A continuous output for 316 range entrance panels. Equipped with internal protection against current overload and short circuits. Dimensions: 106x89x62 mm (6 DIN modules). PSE certified.

The technical specifications are subject to variations without warning.

3453S

STAINLESS STEEL SBC 316 TOUCH A/V ENTRANCE PANEL

ACCESSORIES

3459   ROOF COMPLETE WITH LEDS FOR SENSE 316 ST. STEEL ENT. PANEL

Rain shield for 316 series panels.

1595   33VDC POWER SUPPLY UNIT FOR IKALL ENTRANCE PANEL

Power supply unit with 110-230VAC primary and 33VDC/500 mA continuous output, and 1.2A inrush current for external unit with IKALL entrance panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

The technical specifications are subject to variations without warning.