



1998A

SIMPLEBUS SYSTEM AUDIO PORTER SWITCHBOARD



Desk mounted porter switchboard with 32 character alphanumeric digital keypad. Allows the user code and name to be displayed, keeping the unanswered calls stored in the memory. Day/Night mode and intercom service. It also allows call transmission with indirect codes, management of alarm indications from internal devices. Can be used as a main or secondary switchboard. Up to 1000 names can be stored. 24VAC power supply from part. 1195. Compatible with all Simplebus systems. Dimensions: 158x223x35 mm.



1998A

SIMPLEBUS SYSTEM AUDIO PORTER SWITCHBOARD

MAIN FEATURES

Height (mm):	230
Width (mm):	160
Depth (mm):	100
Operating temperature (°C):	-5 ÷ 40
Maximum current absorption (mA):	200

SOFTWARE/FIRMWARE SPECIFICATIONS

Number of user codes:	1500
No. of storable users:	1500

FUNCTIONS

Alarm function:	Yes
Actuator control function:	Yes
Intercom function:	
Key button function:	Yes

GENERAL DATA

Type of finish:	
Colour:	

COMPATIBILITY

Simplebus 2 audio/video system:	Yes
Simplebus 1 audio system:	Yes

MOUNTING/INSTALLATION

Desk base-mounted:	Yes
--------------------	-----

CONNECTIVITY

Type of connections/ports:	RS232
RS232 ports:	1