

# Enclosed-PFC

75~240W Single Output



SP-240

SP-200

SP-150

SP-100      SP-75

## Features

- Universal AC input / Full range
- Built-in active PFC function, PF>0.93 (SP-240, PF>0.95)
- Protections: Short circuit / Overload / Over voltage / Over temp (SP-150 / 200 / 240)
- Cooling by free air convection (SP-75 / 100 / 150)
- Forced air cooling by built-in DC fan (SP-200 / 240)
- Optional remote ON/OFF control (SP-75~200)
- Built-in fan speed control (SP-200)
- Built-in fan ON/OFF control (SP-240)
- 100% full load burn-in test
- 3 years warranty



(SP-200 only)

## General Specification (Please refer to [www.meanwell.com](http://www.meanwell.com) for detail spec.)

Model No.	SP-75	SP-100	SP-150	SP-200	SP-240
AC input voltage range	85~264VAC, 120~370VDC				88~264VAC, 124~370VDC
AC inrush current (max.)	Cold start, 30A at 230VAC		Cold start, 40A at 230VAC		
DC adjustment range	-5~+10% rated output voltage				±15% rated output voltage
Overload protection	Range: 105%~150%				105%~135%
	Type: Constant current, auto-recovery				Hiccup mode, auto-recovery
Over voltage protection	Range: 115%~135%	110%~135%			120%~150%
	Type: Shut off, AC recycle to re-start				
Withstand voltage	I/P-O/P: 3kVAC, I/P-FG: 1.5kVAC, O/P-FG: 0.5kVAC, 1 minute				
Working temperature	-10~+60°C	-10~+50°C	-10~+60°C	-20~+70°C	
Safety standards	UL60950-1, TUV EN60950-1, GB4943(SP-200 only) approved				
EMC standards	EN55022 class B, EN61000-4-2,3,4,5,6,8,11, EN61000-3-2,3, ENV50204, GB9254(SP-200 only)				
Connection	5P / 9.5mm pitch	7P / 9.5mm pitch terminal block with cover			
Dimension (LxWxH)(mm)	179x99x33	179x99x45	199x99x50	199x99x50	190x93x50
Case No.	920A	915A	916A	916B	987A
Packing	20pcs/12.0kg	20pcs/14.3kg	20pcs/16.4kg	20pcs/17.9kg	18pcs/15.4kg

## 75W

## SP-75

Model No.	Output	Tol.	R&N	Effi.
SP-75-3.3	3.3V, 0~15A	±2%	80mV	68%
SP-75-5	5V, 0~15A	±2%	80mV	72%
SP-75-7.5	7.5V, 0~10A	±2%	80mV	74%
SP-75-12	12V, 0~6.3A	±2%	80mV	77%
SP-75-13.5	13.5V, 0~5.6A	±2%	80mV	78%
SP-75-15	15V, 0~5.0A	±2%	80mV	79%
SP-75-24	24V, 0~3.2A	±1%	100mV	80%
SP-75-27	27V, 0~2.8A	±1%	100mV	80%
SP-75-48	48V, 0~1.6A	±1%	100mV	80%

## 100W

## SP-100

Model No.	Output	Tol.	R&N	Effi.
SP-100-3.3	3.3V, 0~20.0A	±2%	100mV	70%
SP-100-5	5V, 0~20.0A	±2%	100mV	76%
SP-100-7.5	7.5V, 0~13.5A	±2%	100mV	78%
SP-100-12	12V, 0~8.50A	±2%	100mV	80%
SP-100-13.5	13.5V, 0~7.50A	±2%	100mV	80%
SP-100-15	15V, 0~6.70A	±2%	100mV	82%
SP-100-24	24V, 0~4.20A	±1%	150mV	84%
SP-100-27	27V, 0~3.80A	±1%	150mV	83%
SP-100-48	48V, 0~2.10A	±1%	250mV	82%



### 48hrs delivery—

We keep enough stock for 95% of standard models at our 2400m<sup>2</sup> warehouse. We can arrange prompt delivery within 48hrs.

## 150W

## SP-150

Model No.	Output	Tol.	R&N	Effi.
SP-150-3.3	3.3V, 0~30.0A	±2%	100mV	67%
SP-150-5	5V, 0~30.0A	±2%	100mV	75%
SP-150-7.5	7.5V, 0~20.0A	±2%	100mV	79%
SP-150-12	12V, 0~12.5A	±2%	100mV	80%
SP-150-13.5	13.5V, 0~11.2A	±2%	100mV	80%
SP-150-15	15V, 0~10.0A	±2%	100mV	81%
SP-150-24	24V, 0~6.30A	±1%	150mV	83%
SP-150-27	27V, 0~5.60A	±1%	150mV	84%
SP-150-48	48V, 0~3.20A	±1%	250mV	84%

## 200W

## SP-200

Model No.	Output	Tol.	R&N	Effi.
SP-200-3.3	3.3V, 0~40.0A	±2%	100mV	65%
SP-200-5	5V, 0~40.0A	±2%	100mV	71%
SP-200-7.5	7.5V, 0~26.7A	±2%	100mV	76%
SP-200-12	12V, 0~16.7A	±2%	100mV	79%
SP-200-13.5	13.5V, 0~14.9A	±2%	100mV	80%
SP-200-15	15V, 0~13.4A	±2%	100mV	81%
SP-200-24	24V, 0~8.40A	±1%	150mV	83%
SP-200-27	27V, 0~7.50A	±1%	150mV	83%
SP-200-48	48V, 0~4.20A	±1%	250mV	84%

## 240W

## SP-240

Model No.	Output	Tol.	R&N	Effi.
SP-240-5	5V, 0~45A	±2%	150mV	79%
SP-240-7.5	7.5V, 0~32A	±2%	150mV	83%
SP-240-12	12V, 0~20A	±1%	150mV	86%
SP-240-15	15V, 0~16A	±1%	150mV	86%
SP-240-24	24V, 0~10A	±1%	150mV	87%
SP-240-30	30V, 0~8.0A	±1%	150mV	88%
SP-240-48	48V, 0~5.0A	±1%	150mV	89%