

MODEL : SPV-1500-24

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1:150 mVp-p (Max)	I/P: 230VAC O/P:FULL LOAD Ta:25°C	V1: 59 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 22.8V- 25.2V Adjustment by VR	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	22.03 V- 26.07 V/ 230 VAC 22.03 V- 26.07 V/ 115 VAC	P
3	OUTPUT VOLTAGE ADJUST RANGE	CH1: 20%V-110% Adjustment by 1V-6VDC external control	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	5.044 V- 29.05 V/ 230 VAC 4.999 V- 29.1 V/ 115 VAC	P
4	OUTPUT VOLTAGE TOLERANCE	V1: 1%- -1% (Max)	I/P: 100VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.05 %- -0.05 %	P
5	LINE REGULATION	V1: 0.5 %- -0.5 % (Max)	I/P: 100VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0.03 %- -0.03 %	P
6	LOAD REGULATION	V1: 0.5 %- -0.5 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.03 %- -0.03 %	P
7	SET UP TIME	230VAC: 1500 ms (Max)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 535 ms	P
8	RISE TIME	230VAC: 100 ms (Max)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 47 ms	P
9	HOLD UP TIME	230VAC: 14 ms (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 14.5 ms	P
10	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: < 5 %	P
11	DYNAMIC LOAD	V1: 2400 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	2207 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90VAC~264 VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	81V~264V	P
			I/P: LOW-LINE-3V= 87 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 90VAC ~ 264 VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.98 / 115 VAC(TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	PF= 0.965 / 230 VAC PF= 0.998 / 115 VAC	P
4	EFFICIENCY	90 % (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	90.1 %	P
5	INPUT CURRENT	230V/ 8 A (TYP) 115V/ 17 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 7.59 A/ 230 VAC I = 15.32 A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 60 A (TYP) 115V/ 30 A (TYP) COLD START	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 49 A/ 230 VAC I = 25 A/ 115 VAC	P
7	LEAKAGE CURRENT	< 2 mA / 240 VAC	I/P: 264 VAC O/P:Min LOAD Ta:25°C	L-FG: 0.8 mA N-FG: 0.9 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 %~ 135%	I/P: 230 VAC I/P: 115 VAC O/P:TESTING Ta:25°C	122%/ 230 VAC 121%/ 115 VAC Constant Current Limiting	P
2	OVER VOLTAGE PROTECTION	CH1: 30V~ 34.8V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	33.55V/ 230 VAC 33.49V/ 115 VAC Shunt down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	SPEC: TSW2: 105 ± 5°C O.T.P NO DAMAGE	I/P: 230 VAC O/P:FULL LOAD	O.T.P Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE Constant Current Limiting	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT														
1	AUXILIARY POWER (AUX)	12V @ 0.1A (Only for Remote ON/OFF control)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	12.322V	P														
2	REMOTE CONTROL	Table1.1 Fig1.2(a)(b)(c) Specification of Remote ON/OFF	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	<table border="1"> <thead> <tr> <th colspan="2">Connection Method</th> <th>Fig1.2(a)</th> <th>Fig1.2(b)</th> <th>Fig1.2(c)</th> </tr> </thead> <tbody> <tr> <td rowspan="2">SW Logic</td> <td>Output on</td> <td>SW Open</td> <td>SW Open</td> <td>SW Close</td> </tr> <tr> <td>Output off</td> <td>SW Close</td> <td>SW Close</td> <td>SW Open</td> </tr> </tbody> </table>	Connection Method		Fig1.2(a)	Fig1.2(b)	Fig1.2(c)	SW Logic	Output on	SW Open	SW Open	SW Close	Output off	SW Close	SW Close	SW Open	P
Connection Method		Fig1.2(a)	Fig1.2(b)	Fig1.2(c)															
SW Logic	Output on	SW Open	SW Open	SW Close															
	Output off	SW Close	SW Close	SW Open															
3	ALARM SIGNAL OUTPUT	Table2.1 Explanation of alarm <table border="1"> <thead> <tr> <th>Pin</th> <th>POK Alarm</th> </tr> </thead> <tbody> <tr> <td>P OK</td> <td rowspan="2">The signal is "LOW"when ther power supply is above 65%of the rated output voltage</td> </tr> <tr> <td>P OK GND</td> </tr> <tr> <td></td> <td>The signal turns to be "HIGH" when ther power supply is under 65%of the rated output voltage</td> </tr> </tbody> </table>	Pin	POK Alarm	P OK	The signal is "LOW"when ther power supply is above 65%of the rated output voltage	P OK GND		The signal turns to be "HIGH" when ther power supply is under 65%of the rated output voltage	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	<table border="1"> <thead> <tr> <th colspan="2">Output of alarm</th> </tr> </thead> <tbody> <tr> <td>Good:Low</td> <td>(0.5V max at 10mA)</td> </tr> <tr> <td>Fail:High or open</td> <td>(50V 10mA max)</td> </tr> </tbody> </table>	Output of alarm		Good:Low	(0.5V max at 10mA)	Fail:High or open	(50V 10mA max)	P	
Pin	POK Alarm																		
P OK	The signal is "LOW"when ther power supply is above 65%of the rated output voltage																		
P OK GND																			
	The signal turns to be "HIGH" when ther power supply is under 65%of the rated output voltage																		
Output of alarm																			
Good:Low	(0.5V max at 10mA)																		
Fail:High or open	(50V 10mA max)																		
4	CURRENT SHARING	PSU1-PSU2 < 10%	I/P: 230 VAC O/P:FULL/50% LOAD Ta:25°C	PV=5V: 1.O/P:100% PSU1: 1500 W (PIN W) PSU2: 1480 W (PIN W) PSU3: 1530 W (PIN W) 2.O/P:50% PSU1: 800 W (PIN W) PSU2: 787 W (PIN W) PSU3: 853 W (PIN W) PV=3V: 1.O/P:100% PSU1: 973 W (PIN W) PSU2: 960 W (PIN W) PSU3: 959 W (PIN W) 2.O/P:50% PSU1: 530 W (PIN W) PSU2: 525 W (PIN W) PSU3: 552 W (PIN W) PV=1V: 1.O/P:100% PSU1: 360 W (PIN W) PSU2: 353 W (PIN W) PSU3: 361 W (PIN W) 2.O/P:50% PSU1: 199 W (PIN W) PSU2: 200 W (PIN W) PSU3: 200 W (PIN W)	P														
5	REMOTE SENSE	>0.25V	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	> 0.25 V	P														
6	OUTPUT VOLTAGE TRIM	4.8 V- 28 V	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	OK	P														

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																									
1	TEMPERATURE RISE TEST	MODEL : SPV-1500-24 1. ROOM AMBIENT BURN-IN : 1 HRS I/P: 230VAC O/P: FULL LOAD Ta= 33.8 °C 2. HIGH AMBIENT BURN-IN : 3 HRS I/P: 230VAC O/P: FULL LOAD Ta= 51.8 °C																																																																																																												
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>HIGH AMBIENT FULL LOAD Ta= 33.8 °C</th> <th>HIGH AMBIENT FULL LOAD Ta= 51.8 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF2</td><td>TR541-R2 W523</td><td>45.5°C</td><td>62.8°C</td></tr> <tr><td>2</td><td>BD2</td><td>25A/600V GLASS D25XB60</td><td>52.9°C</td><td>70.0°C</td></tr> <tr><td>3</td><td>L1</td><td>TF1198-R1 ETD-39</td><td>49.1°C</td><td>65.1°C</td></tr> <tr><td>4</td><td>Q7</td><td>SPW20N60C3 20.7A/600V TO247</td><td>39.8°C</td><td>57.4°C</td></tr> <tr><td>5</td><td>D2</td><td>STTH3006DPI 30A/600V DOP3I</td><td>49.2°C</td><td>66.1°C</td></tr> <tr><td>6</td><td>U3</td><td>TNY280PN DIP-8C</td><td>50.7°C</td><td>69.5°C</td></tr> <tr><td>7</td><td>C18</td><td>150u/450V 105°C 25*30 MXG</td><td>40.5°C</td><td>57.6°C</td></tr> <tr><td>8</td><td>T900</td><td>TF1315-R5 ETD-39</td><td>62.7°C</td><td>80.3°C</td></tr> <tr><td>9</td><td>L900</td><td>TF1201-R2 ER-28</td><td>77.2°C</td><td>98.3°C</td></tr> <tr><td>10</td><td>D900</td><td>YS065W WS-AP017</td><td>56.1°C</td><td>75.5°C</td></tr> <tr><td>11</td><td>LF900</td><td>TR545-R5 T22x14x8 1000u</td><td>55.7°C</td><td>75.4°C</td></tr> <tr><td>12</td><td>C900</td><td>150u/450V 105°C 25*30 MXG</td><td>53.9°C</td><td>73.4°C</td></tr> <tr><td>13</td><td>Q901</td><td>FQA24N50 24A/500V TO3P</td><td>70.2°C</td><td>95.7°C</td></tr> <tr><td>14</td><td>L102</td><td>TR595-R1 Ku106060-2 43.2u</td><td>49.6°C</td><td>67.7°C</td></tr> <tr><td>15</td><td>D104</td><td>60CPQ150 60A/150V TO247</td><td>58.6°C</td><td>75.7°C</td></tr> <tr><td>16</td><td>C116</td><td>1000u/35V UL10Kh 12.5*20 ZLH</td><td>45.3°C</td><td>63.1°C</td></tr> <tr><td>17</td><td>C118</td><td>1000u/35V UL10Kh 12.5*20 ZLH</td><td>47.2°C</td><td>65.0°C</td></tr> <tr><td>18</td><td>TSW2</td><td>ST-22W-R1 105°C 90mm HH(8821)</td><td>65.9°C</td><td>90.3°C</td></tr> <tr><td>19</td><td>U2</td><td>UC3855BDW SOIC-20</td><td>44.4°C</td><td>62.0°C</td></tr> <tr><td>20</td><td>U100</td><td>UCC2895DW SOIC-20</td><td>46.8°C</td><td>65.0°C</td></tr> </tbody> </table>	NO	Position	P/N	HIGH AMBIENT FULL LOAD Ta= 33.8 °C	HIGH AMBIENT FULL LOAD Ta= 51.8 °C	1	LF2	TR541-R2 W523	45.5°C	62.8°C	2	BD2	25A/600V GLASS D25XB60	52.9°C	70.0°C	3	L1	TF1198-R1 ETD-39	49.1°C	65.1°C	4	Q7	SPW20N60C3 20.7A/600V TO247	39.8°C	57.4°C	5	D2	STTH3006DPI 30A/600V DOP3I	49.2°C	66.1°C	6	U3	TNY280PN DIP-8C	50.7°C	69.5°C	7	C18	150u/450V 105°C 25*30 MXG	40.5°C	57.6°C	8	T900	TF1315-R5 ETD-39	62.7°C	80.3°C	9	L900	TF1201-R2 ER-28	77.2°C	98.3°C	10	D900	YS065W WS-AP017	56.1°C	75.5°C	11	LF900	TR545-R5 T22x14x8 1000u	55.7°C	75.4°C	12	C900	150u/450V 105°C 25*30 MXG	53.9°C	73.4°C	13	Q901	FQA24N50 24A/500V TO3P	70.2°C	95.7°C	14	L102	TR595-R1 Ku106060-2 43.2u	49.6°C	67.7°C	15	D104	60CPQ150 60A/150V TO247	58.6°C	75.7°C	16	C116	1000u/35V UL10Kh 12.5*20 ZLH	45.3°C	63.1°C	17	C118	1000u/35V UL10Kh 12.5*20 ZLH	47.2°C	65.0°C	18	TSW2	ST-22W-R1 105°C 90mm HH(8821)	65.9°C	90.3°C	19	U2	UC3855BDW SOIC-20	44.4°C	62.0°C	20	U100	UCC2895DW SOIC-20	46.8°C	65.0°C	P
NO	Position	P/N	HIGH AMBIENT FULL LOAD Ta= 33.8 °C	HIGH AMBIENT FULL LOAD Ta= 51.8 °C																																																																																																										
1	LF2	TR541-R2 W523	45.5°C	62.8°C																																																																																																										
2	BD2	25A/600V GLASS D25XB60	52.9°C	70.0°C																																																																																																										
3	L1	TF1198-R1 ETD-39	49.1°C	65.1°C																																																																																																										
4	Q7	SPW20N60C3 20.7A/600V TO247	39.8°C	57.4°C																																																																																																										
5	D2	STTH3006DPI 30A/600V DOP3I	49.2°C	66.1°C																																																																																																										
6	U3	TNY280PN DIP-8C	50.7°C	69.5°C																																																																																																										
7	C18	150u/450V 105°C 25*30 MXG	40.5°C	57.6°C																																																																																																										
8	T900	TF1315-R5 ETD-39	62.7°C	80.3°C																																																																																																										
9	L900	TF1201-R2 ER-28	77.2°C	98.3°C																																																																																																										
10	D900	YS065W WS-AP017	56.1°C	75.5°C																																																																																																										
11	LF900	TR545-R5 T22x14x8 1000u	55.7°C	75.4°C																																																																																																										
12	C900	150u/450V 105°C 25*30 MXG	53.9°C	73.4°C																																																																																																										
13	Q901	FQA24N50 24A/500V TO3P	70.2°C	95.7°C																																																																																																										
14	L102	TR595-R1 Ku106060-2 43.2u	49.6°C	67.7°C																																																																																																										
15	D104	60CPQ150 60A/150V TO247	58.6°C	75.7°C																																																																																																										
16	C116	1000u/35V UL10Kh 12.5*20 ZLH	45.3°C	63.1°C																																																																																																										
17	C118	1000u/35V UL10Kh 12.5*20 ZLH	47.2°C	65.0°C																																																																																																										
18	TSW2	ST-22W-R1 105°C 90mm HH(8821)	65.9°C	90.3°C																																																																																																										
19	U2	UC3855BDW SOIC-20	44.4°C	62.0°C																																																																																																										
20	U100	UCC2895DW SOIC-20	46.8°C	65.0°C																																																																																																										
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: O/P SHORT TEST Ta:37.6°C	TEST : OK	P																																																																																																									
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 100% LOAD Ta= -20°C	TEST : OK	P																																																																																																									
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 50°C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																																									
5	TEMPERATURE COEFFICIENT	± 0.05 % (0-50°C)	I/P: 230 VAC O/P: O/P SHORT TEST Ta:37.6°C	± 0.01 % (0-50°C)	P																																																																																																									
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																																																																									

LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 109K HRS			P
2	CAPACITOR LIFE CYCLE	SPV-1500-24 : SUPPOSE C118 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25 °C LIFE TIME= 1228729 HRS I/P: 230VAC O/P:FULL LOAD Ta= 50 °C LIFE TIME= 220279 HRS			P

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3 KVAC/min I/P-FG: 1.5 KVAC/min O/P-FG: 0.5 KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-O/P: 11.81 mA I/P-FG: 8.63 mA O/P-FG: 14.67 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C /70%RH	I/P-O/P: 1.65 GΩ I/P-FG: 2.87 GΩ O/P-FG: 6.5 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta:25°C / 70%RH	7 mΩ	P
4	APPROVAL	TUV : Certificate NO : R50063850 UL : File NO : E183223			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS D	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ)/115V(60HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ)/115V(60HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N : 1KV L,N-PE : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q900 Rated FOA24N50 : 500V 24 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 430 V (2) 408 V (3) 472 V	P
2	Diode Peak Voltage	D102 Rated 60CPQ150 : 150V 60A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 105 V (2) 98 V (3) 88.8 V	P
3	Input Capacitor Voltage	C15 Rated : 150 u / 450V/ 105°C	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change (4)Burn in 1hour Ta:25°C	(1) 376 V (2) 389 V (3) 389 V (4) 389 V	P
4	Control IC Voltage Test	U100 Rated UCC2895W : 9.8V-18.5 V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 10.81-11.1 V (2) 11.97-12.03 V (3) 12.03 V	P
5	PFC Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated SPW20N60C3 20.7A/600V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25°C	(1) 460 V (2) 450 V (3) 482 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2009/6/5	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2009/7/31	PRODUCT SAMPLE W0906D50	PASS	SANFORD SU	VINCENT TSENG

2003/12/12 A50-F023