

AS586XXL

Outdoor siren - The Level - blue base / no cover / no battery



Details

- Spirit level on top of the back plate to correctly align the AS580
- Low profile polycarbonate box with integrated strobe lens
- Double piezo sounder with 112 dB @ 1m sound output
- Highly weather resistant, IP55
- Easy wiring
- Easy diagnostics using the LEDs
- Tamper switch to protect from removal of cover or removal from surface

AS586XXL

Outdoor siren - The Level - blue base / no cover / no battery

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren

Electrical

Operating voltage	10 to 14.5 V
Current consumption	350 mA

Physical

Physical dimensions	371 x 225 x 56 mm
---------------------	-------------------

Environmental

Operating temperature	-25 to 55 °C
-----------------------	--------------

Standards & regulation

Compliancy	CE
------------	----

Material

Polycarbonate

PCB protection

Fully potted

Power supply

10.0V - 14.5V

Tamper & pry-off

Yes

Typical standby current

LEDs OFF:	38 mA
LEDs ON alt:	57 mA
LEDs ON cont:	74 mA

Typical operating current

Sounder:	350 mA
Flash light:	110 mA
Sounder + Flash:	420 mA

Sounder

Double piezo

Sound output

112 dBA

Sounder cut-off timer

5' or 15'

Frequency

1.8 to 3 kHz

Operating temperature

-25 to +55°C

Dimensions

371 x 225 x 56 mm

Battery

BS120N-XXL- Lead acid 12V - 0.8Ah
(to be ordered separately)

