DATA SHEET

COD. 2619

SIMPLEBUS STYLE INTERCOM HANDSET

Entry phone with electronic call, conversation button on base, call volume control, privacy function, and conversation privacy. Equipped with a series of key buttons and a further 8 buttons for intercom function or various services (2 of the buttons can be used as a C/N.O contact). Equipped with LED that may be used for various signals (busy, doctor function). Complete with 8-position dip switch for selection of the desired user code. Door entry phone for use in all Simplebus systems. Allows management of floor door call, call repeat, sending of alarm signals to the porter switchboard, call to main switchboard, secondary switchboard and guardian door entry-phone. Allows direct intercom calls between users with the use of an interface or porter switchboard and the use of a number of relay actuators; programming of buttons does not require dedicated programmers. Fitted with terminal art. 1214/2C. The fascia can be changed on this model. Dimensions: 95x215x58 mm.



General specifications

System:	SBT S1 S2(2-wires)
Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	No
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	No
Induction loop function:	No
Product colour:	White RAL9003, cover light blue
Interchangeable cover:	Yes
Sensitive Touch technology:	No
Total buttons:	9
Additional buttons:	No
LED signaling:	1
Led to additional signaling:	No

Functions

Actuator control function:	Yes
Switchboard call function:	Yes
Panic call:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Call to group addresses:	Yes
Call forwarding:	Yes
Privacy function:	Yes



The technical specifications are subject to variations without warning

DATA SHEET

	Doctor:	Yes
	Redial:	Yes
	Floor door call function:	Yes
	Electronic bell:	Yes
	Mechanical ringtone:	No
	Customisable ringtone:	Yes
	Alarm function:	No
	Privacy conversation function:	Yes
	Key button function:	Yes
	Full Duplex hands-free function:	No
Hard	ware specifications	
	Customisable housing:	Yes
Setti	nas	
••••	Loudspeaker volume control:	Yes
	Microphone volume control:	Yes
	Ringtone volume control:	Yes
Gene	eral info	
	Product height (mm):	215
	Product width (mm):	95
	Product depth (mm):	58
Com	patibility	
•••••	Simplebus Top system:	Yes
Tech	nical specifications	
	Power supply voltage:	22÷28Vdc
	Absorption:	1
	Maximum current absorption (mA):	200
	Microphone:	9,6x6,9mm omni-direction
	Loudspeaker:	50mm 50OHM
	IP Rating:	30
	Operating temperature (°C):	-5÷40
	Product weight (g):	0,55
	Clamps:	L L CFP CFP LED+ LED- SS+ C8 P8 C9 P9
	· ·	
Pack	aging	
	Single pack height (mm):	65
	Single pack width (mm):	235
	Single pack weight (Kg):	0,55
	Single pack depth (mm):	90



The technical specifications are subject to variations without warning

DATA	SHE	EET
------	-----	-----

Single pack volume (dm3):

1,375



The technical specifications are subject to variations without warning