

MINI MONITOR WITH HANDSET. BLACK. SBTOP SYSTEM

Wall-mounted monitor with 4.3" 16/9 colour screen and handset. Allows brightness and colour control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with 8 soft touch buttons for door-opening, self-ignition, switchboard call and privacy service functions and with door status indicator LEDs. Manages floor door calls as standard. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Includes wall-mounting or residential series box backplate and riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire SimplebusTop Color systems. Dimensions: 175x160x22mm.



Main specifications

Audio/video system:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	No
Type of display:	LCD
Display size (inches):	4,3" 16:9
Display resolution (H x V):	480x272 pixel
B/W or colour display:	Colors
Product colour:	Black
Sensitive Touch technology:	Yes
Total buttons:	8
Additional buttons:	1
LED signaling (No.):	2
Backlighting color:	White

Functions

Actuator control function:	Yes
Self-ignition:	Yes
Switchboard call function:	Yes
Panic call:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Call forwarding:	Yes
Privacy function:	Yes
Doctor:	Yes

DATA SHEET

Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	Yes
Privacy conversation function:	Yes
Key button function:	Yes

Hardware specifications

Removable terminals:	Yes
----------------------	-----

Settings

Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes
Display brightness control:	Yes
Display contrast control:	No
Display colour control:	Yes

General data

Product height (mm):	160
Product width (mm):	175
Product depth (mm):	22

Compatibility

Simplebus Top audio/video system:	Yes
-----------------------------------	-----

Technical specifications

Power supply voltage:	28 ÷
Maximum current absorption (mA):	200
IP Rating:	IP30
Operating temperature (°C):	40 ÷
RH max operating humidity (%):	75 ÷
Video encoding:	PAL/NTSC
Product weight (g):	0,65
Clamps:	L L CFP1 CFP2