DATA SHEET

COD. 4894E

ENTRANCE PANEL 1 EASYCALL CALL FOR VIP SYSTEM

Internal entrance panel equipped with call button. Metal finish. Surface-mounted installation. Dimensions: 90x160x28 mm



Main specifications

| Audio system: | Yes |
|------------------------------------|-----------------------------------|
| Wall-mounted: | Yes |
| Power supply: | PoE (Class 0) / VIP (37 ÷ 57 VDC) |
| Maximum current absorption (mA): | 61 |
| Clamps: | GND AL CFP S- S+CN1 |
| Buttons to call: | Yes |
| Total buttons: | 1 |
| Loudspeaker volume control: | Yes |
| Operating temperature (°C): | -5 ÷ |
| RH max operating humidity (%): | 25 ÷ 75 |
| Network connection: | RJ45 |
| IP protection rating: | IP30 |
| Vandal Resistant rating (IK code): | |
| Backlighting color: | Blu |

Software/firmware specifications

| IP assignment: | AutoIP, DHCP, Static IP |
|------------------------|-------------------------|
| No. user codes: | 1 |
| No. of storable users: | 1 |

Hardware specifications

| Visual signalling: | Yes |
|----------------------|-----|
| Acoustic signalling: | Yes |

General data

POE power supply: 36-57 Vdc, standard PoE



DATA SHEET

| Product height (mm): | 160 |
|----------------------|-----|
| Product width (mm): | 90 |
| Product depth (mm): | 28 |

Compatibility

Vip system: Yes

Connectivity

| Type of connections/ports: | Ethernet |
|----------------------------|----------|
| Ethernet ports: | 1 |

