

## EASYCOM SIMPLEBUS UNIT - WHITE

Hands-free audio unit with electronic call, call volume adjustment, privacy service, loudspeaker volume adjustment and conversation privacy. Fitted with 3 buttons for audio operation, with audio active indicator LED, lockrelease command and command for actuator part. 1256. The buttons can be configured differently for switchboard call and actuator functions. Allows door bell and call repetition management. Complete with DIP switch with 8 positions for selection of the desired user code. Compatible with all SimpleBus systems and Kits. Fitted with distribution terminal part. 1214/2C. Colour: white. Dimensions: 90x160x28 mm.



### Main specifications

Audio system:	Yes
Audio/video system:	Yes
Flush-mounted:	No
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Induction loop function:	No
Sensitive Touch technology:	No
Total buttons:	3

### Functions

Actuator control function:	Yes
Switchboard call function:	Yes
Panic call:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Privacy function:	Yes
Doctor:	Yes
Redial:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	No
Alarm function:	No
Privacy conversation function:	Yes
Key button function:	Yes

# DATA SHEET

## Hardware specifications

Customisable housing:	No
-----------------------	----

## Settings

Loudspeaker volume control:	Yes
-----------------------------	-----

Microphone volume control:	Yes
----------------------------	-----

Ringtone volume control:	Yes
--------------------------	-----

## General data

Product height (mm):	160
----------------------	-----

Product width (mm):	90
---------------------	----

Product depth (mm):	28
---------------------	----

## Compatibility

Simplebus Top audio/video system:	Yes
-----------------------------------	-----

Simplebus 2 audio system:	Yes
---------------------------	-----

## Technical specifications

Power supply voltage:	22 ÷ 28
-----------------------	---------

Absorption:	0,7
-------------	-----

Maximum current absorption (mA):	400
----------------------------------	-----

Microphone:	9,6x9,6mm omni-direction
-------------	--------------------------

Loudspeaker:	50mm 50OHM
--------------	------------

IP Rating:	IP30
------------	------

Operating temperature (°C):	5 ÷ 40
-----------------------------	--------

Product weight (g):	355
---------------------	-----

Clamps:	L L CFP CFP S- S+
---------	-------------------