

DATA SHEET

COD. 6228B

EASYCOM SIMPLEBUS UNIT - BLACK

Hands-free audio unit with electronic call, call volume adjustment, privacy service, loudspeaker volume adjustment and conversation privacy. Fitted with 3 buttons for audio operation, with audio active indicator LED, lockrelease command and command for actuator part. 1256. The buttons can be configured differently for switchboard call and actuator functions. Allows door bell and call repetition management. Complete with DIP switch with 8 positions for selection of the desired user code. Compatible with all SimpleBus systems and Kits. Fitted with distribution terminal part. 1214/2C. Colour: black. Dimensions: 90x160x28 mm.



Main specifications

| | |
|----------------------|---------------|
| Audio system: | Yes |
| Audio/video system: | Yes |
| Wall-mounted: | Yes |
| Desk base-mounted: | Yes |
| Hands-free function: | Yes |
| Product colour: | Black RAL9005 |
| Total buttons: | 3 |
| Backlighting color: | Blu |

Functions

| | |
|-----------------------------|-----|
| Actuator control function: | Yes |
| Switchboard call function: | Yes |
| Panic call: | Yes |
| Intercom function: | Yes |
| Selective intercom call: | Yes |
| Call to multiple addresses: | Yes |
| Privacy function: | Yes |
| Doctor: | Yes |
| Redial: | Yes |
| Floor door call function: | Yes |
| Electronic bell: | Yes |
| Customisable ringtone: | Yes |

Settings

| | |
|-----------------------------|-----|
| Loudspeaker volume control: | Yes |
| Microphone volume control: | Yes |

DATA SHEET

Ringtone volume control: Yes

Compatibility

Simplebus Top audio/video system: Yes

Technical specifications

Power supply voltage: 22 ÷ 28

Absorption: 0,7

Maximum current absorption (mA): 400

Microphone: 9,6x9,6mm omni-direction

Loudspeaker: 50mm 50OHM

IP Rating: IP30

Operating temperature (°C): 5 ÷ 40

Product weight (g): 355

Clamps: L L CFP CFP S- S+