

MOVEMENT DETECTOR

220 SM



General information

SKU	C4-KNX-WD220-AP
Catalog description	Movement Detector 220 SM , alpine white, surface-mounted
Long description	With 2 movement detection channels. With 1 twilight channel and 3 switching thresholds. Includes integrated KNX bus coupler. No additional power supply necessary. Surveillance density: 92 sectors with 368 switching segments. Twilight sensor: approx. 1 - 1000 lux. Switch-off delay: approx. 10 sec to 1092 min. Sensor angle: 220°. Range: approx. 16 m.
Number of batteries	0

Dimensions

Product (H × W × D)	115 × 125 × 141 mm
Product net weight	0.54 kg


Package

Package type	Level 1	Level 2	Level 3
Unit count	1 ct.	10 ct.	180 ct.
Package (H × W × D)	145 × 137 × 175 mm	300 × 325 × 419 mm	1065 × 800 × 1200 mm
Package gross weight	0.54 kg	5.755 kg	123.59 kg

Additional information

RoHS status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Product main type	Surface-mounted presence detector
Product name	Movement Detector 220 SM
RoHS date	20160624

MOST RECENT VERSION



ctrl4.co/knx-wd220-ds