

PRESENCE DETECTOR

MINI FM



General information

SKU	C4-KNX-MPD-ST
Catalog description	Presence Detector Mini FM, studio white matte, surface-mounted
Long description	Detection range (circular) for mounting heights 2.5 m, 3 m, and 4 m. Seated persons Ø: max 5 m, max 6.5 m, and max 9 m, respectively. Walking persons Ø: max 6.5 m, max 8 m, and max 10.5 m, respectively. Visible height: 16 mm. 2 channels. Targeted for connection and disconnection of light bands depending on the room brightness. Regulation in response to movement possible. Use the device as presence and/or movement detector. Detector application with 2 power-off stages. Detector application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. Includes integrated KNX bus coupler. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flush-mounted box.
Number of batteries	0


Dimensions

Product (H × W × D)	80 × 80 × 45 mm
Product net weight	0.131 kg

Package

Package level 1 units	1 piece
Package (H × W × D)	62 × 86 × 113 mm
Package level 1 gross weight	0.131 kg

MOST RECENT VERSION



ctrl4.co/knx-mpd-ds

Additional information

RoHS status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Product main type	Surface-mounted presence detector
Product name	Presence Detector Mini FM
RoHS date	20160624