

Control4® Remote Recharging Station



Control4® SR260 Remote and Recharging Station (C4-SR260RSK)

Control4® SR260-I Remote and Recharging Station (C4-SR260RSK-I)

Control4® SR-250 Remote and Recharging Station (C4-SR250RSK-B)

Control4® SR-150 Remote and Recharging Station (C4-SR150RSK-B)

The Control4® SR260/SR-250/SR-150 Remote and Recharging Station keeps your system remote control ready with a fully charged battery, always. Using Lithium-Polymer technology and an elegant charging station, customers no longer have to worry about searching for batteries so they can turn on their system. Features include:

- Low-profile charging cradle
- Inconspicuous charging indicator that can be dimmed or turned off
- Magnetic charging cradle and battery cover assures proper seating of remote control when charging
- Lithium-Polymer battery provides hundreds of charge cycles for years of performance
- Available accessories:
 - › Recharging Station for Existing SR260/SR-250/SR-150 Remote (C4-SRRS)
 - › SR260/SR-250 Rechargeable Battery and Cover (C4-RBATT-250)
 - › SR-150 Rechargeable Battery and Cover (C4-RBATT-150)



Control4 Remote and Recharging Station

	SR260/SR260-I/SR-250 Remote and Recharging Station	SR-150 Remote and Recharging Station	Recharging Station only	SR260/SR-250 Rechargeable battery and cover	SR-150 rechargeable battery and cover
Model number	C4-SR260RSK C4-SR260RSK-I C4-SR250RSK-B	C4-SR150RSK-B	C4-SRRS	C4-RBATT-250	C4-RBATT-150
Battery type	Lithium-Polymer	Lithium-Polymer	N/A	Lithium-Polymer	Lithium-Polymer
Power requirements	DC Supply 5V@1A, Mini-USB type connector Input			N/A	N/A
Dimensions (W×H×D)	2.5" × 2" × 9"	2.5" × 2" × 9"	N/A	N/A	N/A
Humidity	5% - 90% Non-Condensing				
Operating temperature	40°F - 90°F (4°C - 32°C)				
Storage temperature	0°F - 100°F (-18°C - 38°C)				

For product photos, documentation, and setup instructions, visit: ctrl4.co/docs